



ACCUSPRAY

Designed for performance and ease, the Accuspray Boomspray is self-levelling and features a single axle on air bag suspension to provide a superior ride and more durable boomspray. Wings operate independently from the main chassis, and nitrogen-charged accumulators create a smooth journey on any terrain. Built for maximum lifespan and to withstand corrosion, the Accuspray Boom spray features high grade stainless steel hardware and is finished with two pace primer and enamel.

A stainless steel manifold located on one side of the unit means a central access for all the taps to see at a glance exactly what you have set up, make changes without walking around the unit. It's simple and easy to operate. Resulting in less chemical contamination and makes tank flushing and maintenance easier.

To give you a superior ride, we've designed a self-levelling suspension system that out performs others in the market. Every Accuspray Boomsprays incorporates a self-levelling suspension system allowing the wings to operate independently to the main chassis, reducing boom sway, wear and tear. This feature also ensures your chemical is more evenly distributed to the target area.

All Accuspray boom sprays now have a Proportional Controlled hydraulic boom function. Which means when activating wing fold procedure you can control the speed of the wing. This eliminates any unsightly jerking motions when folding.

With a variety of optional extras, like the cutting edge and cost saving Seletron spraying system, Titan Engineering is sure to deliver an Accuspray Boomspray to meet your exact needs. Our team is dedicated to delivering an exceptional product with unrivalled back up and service.



CONVENIENT GREASE BANKS



BOOM RECYCLING



AIR MAGIC NOZZLES



NO ROAD ESCORT REQUIRED

Peter Harvey
Titan Engineering

M: 0428891200

O: 08 98891200

F: 08 98891250

PO Box 102

Kondinin WA 6367

www.accuspray.com.au

peter@middleeast.com.au



FEATURES

- 2 year structural warranty
- Single 110 diameter axle
- Air bag suspension self adjusting
- Stainless steel manifold for easy access and usage
- Hydraulic fold and boom tilt
- Chemical resistant hose
- Power Plastic chemical resistant hydraulic hose
- Can spray at full height
- Self-leveling system for boom stability
- High grade stainless steel bolts, nuts and hose clamps
- Arag electric valves used Stainless steel motorized ball valve taps
- Wing tip breakaways Hypro pump
- Hydraulic lift to 2.3m Independent secondary wing fold
- 30ltr hand wash tank
- Correctly charged hydraulic accumulator for smooth ride
- Coil shock absorbers on outrigger wheels
- Tank sprinkler
- All Viton seals
- Booms are sandblasted before sealing with two-pac primer and Enamel top coats
- Single or twin spray lines
- Flexi-N compatible componentry
- Stainless steel clamps on jet bodies Jets protected by boom arms
- Hand rails and steps
- Machine fully water tested before delivery
- Triple filtration system
- 200ltr sealed tool box

OPTIONS

- 90 to 150 ft boom widths
- 5000, 7000, 8500 and 10000L spray tanks
- Flush on-the-go
- Chemical transfer pump
- Single or Twin spraying lines
- Multiple spray sections
- Granny pot with venturie
- Multiple spray controller brands
- Isobus controlled
- Boom recirculating Air switching
- 500 or 1000L flush tank
- Work lights
- Rear Tow Hitch



OPTIONAL GRANNY POT



90 TO 150 FT BOOM WIDTHS

SPECIFICATIONS

Spray tank volume	Working widths (in meters)	Transport widths (in meters)	Transport heights (in meters)	Overall length (in meters)	Draw bar to axle length (in meters)	Wheel track width (in meters)	Total weight (in kg)	Tyre size	Suspension type	Flush tank	Product Pump
5000L	27, 30, 33, 36m	3.5m (no escort required)	3.95m	10.8m	7.7m	2.37m or 3m	4000kg	520/85 R38		500 or 1000L	
7000L	27, 30, 33, 36m	3.5m (no escort required)	3.95m	10.8m	7.7m	2.37m or 3m	4100kg	520/85 R42	Air bag	500 or 1000L	Arag MP400 Centrifical
10000L	40 to 45m	3.76 or 3.59m	4.1m	12.6m	9.4m	3m	5700kg	710/70 R42 or 650/65R38		500 or 1000L	